

SurgiTable 4

Electro-Hydraulic Operating Table



For standard & ergonomic low-height positioning




SurgiTable 4 is an electro-hydraulic operating table designed to meet universal surgicalpositioning needs, like in Neurology, Ophthalmology, Gynecology, Urology, Minimal Invasive Surgery, Hand & Arm surgeries, etc.

For ergonomic convenience, the low-height version of SurgiTable 4 is specially developed for those procedures requiring lower table height, like in Neurology, Ophthalmology, ENT, laparoscopic and other minimal access surgeries.

Both systems are equipped with high-performances electro-hydraulic lift systems, height and position can be easily set up and adjusted with corded remote controlled.

Besides AC power supply, optional battery is also available for backup use up to 50 batches of procedures if AC is unexpectedly lost, which doubly boosts the surgical safety during operation.



Features



- Corded Remote controller with Auto-lock function to avoid accidental mis-operation



- Memory foam pad covered with antibacterial surface



 Optional battery for backup in case of unexpected lose of AC power supply

- Front-ended brake and release for move

- AC power supply



- Detachable leg section for orthopedic extension or gynecology/urology application



- Patient load up to 200kg during positioning movement



 Durable SUS304 grade stainless steel material



 Comprehensive accessories and attachments to meet various positioning needs



Accessories



- Leg support,padded. Also called Knee Crutch. Used to support patient's leg in lithotomy or sitting position.



- Lateral support,padded. Also called Lateral Brace. Hexagonal rod. Used to support patient's body insupine, prone and lateral position.



- Shoulder Support, padded. Also called Shoulder rest / brace. Hexagonal rod. Used to prevent shoulder injury and restrict patient's movement.



- L-shaped anesthesia screen, Stainless steel made, rigid-Installed with square clamp.



- Easy armboard. Used to support patient arm, installed with quickrelease clampsnaping onto the side rail.- Horizontal adjustment 180°, padded.



- Body restraint strap. Used to restrict the movement of a patient during surgical procedure.




Specification

Model Name	SurgiTable 4 (Standard)	SurgiTable 4 (Low position)	
Table length	2100 mm	2100 mm 500 mm (not include side-rail)	
Table width	500 mm (not include side-rail)		
Table height (Raised/Lowered)	1040 mm / 690 mm	800 mm / 550 mm	
Trendelenburg/ Reverse-trendelenburg	25 ° / 25 °	25 ° / 25 °	
Lateral tilt (right/left)	20 ° / 20 °	20°/20°	
Back plate (up/down)	80°/12°	80°/12°	
Head plate (up/down)	90 ° /90 °	90 ° /90 ° 10 ° / 100 ° / 100 ° x2	
Leg plate (up/down/split)	10°/100°/100°x2		
Flex / Reflex	192°/100°	192°/100°	
Patient weight	200 kg (during positioning)	200 kg (during positioning)	
Input power	AC 110/220V, 60/50Hz	AC 110/220V, 60/50Hz	

Other products ·

	Pic	Table Model.	Lifting system	Positioning	Surgery type
The second	A	SurgiTable 1	Hydraulic	Motor	Universal use (especially for imaging)
-		SurgiTable 4 (Standard)	Hydraulic	Motor	Universal Use
-		SurgiTable 4 (Low position)	Hydraulic	Motor	Universal Use (especially for surgeries requiring low height: neurology, ENT, ophtalmology, laparoscopic surgery)
_		SurgiTable 200	Hydraulic	Manual	Universal use

ATA LED





For more information: contact@ata-medical.om / www.ata-surgical.com